







# Lay-Flat Fire Hose Catalogue

Effective date: Jun-20

Product	Description	Inside Diameter	Coupling type & size	Diameter when rolled using ANCO rewinder	Manufacturer's rated maximum burst pressure	Certification	Picture
25mm <b>Forester</b> Heavy Duty Lay-Flat	Synthetic woven canvas, self percolating	25mm	25mm Geka	360mm	3500 KPA	SABS 1456 Part 3	
38mm <b>Forester</b> Heavy Duty Lay-Flat	Synthetic woven canvas, self percolating	38mm	38mm BIC Instantaneous	380mm	3500 KPA	SABS 1456 Part 3	
25mm <b>ATLAS</b> Heavy Duty Lay-Flat	High tenacity polyester woven, non percolating, full synthetic black inner	25mm	25mm Geka	430mm	90 Bar - burst / 20 Bar Working	ISO9002	
38mm <b>ATLAS</b> Heavy Duty Lay-Flat	High tenacity polyester woven, non percolating, full synthetic black inner	38mm	38mm BIC Instantaneous	430mm	90 Bar - burst / 20 Bar Working	ISO9002	




# Lay-Flat Fire Hose Catalogue

**Non-Percolating Hose (Dry exterior)**

Effective date:

Jul-19

Product	Description	Inside Diameter	Coupling type & size	Coiled diameter when rolled using ANCO rewriter	Manufacturer's rated maximum burst pressure	Certification	Picture
25mm <b>Eschbach Polydur</b> Lay-Flat	Full synthetic, non-percolating, Extra Heavy Duty	25mm	25mm Geka	580mm	50 Bar - Burst / 17 Bar - Working	DIN14811 Part 3	
38mm <b>Eschbach Polydur</b> Lay-flat	Full synthetic, non-percolating, Extra Heavy Duty	38mm	38mm BIC Instantaneous OR 63mm BIC Instantaneous - <b>please specify</b>	600mm	50 Bar - Burst / 17 Bar - Working	DIN14811 Part 3	