

ANCO MANUFACTURING

2625 Theo Mocke Street, Piet Retief, 2380
P.O. Box 882, Piet Retief, 2380, South Africa

Tel: +27 17 826 6023

www.ancoman.co.za



HP200 Compact-Slip-on Unit (Bakkie Sakkie)

TYPICAL APPLICATIONS:

- Designed to optimise available load-bin space on modern double cab LDV's while still having effective fire fighting capabilities. Estimated 200L tank capacity allows forestry managers & contractors to react as first responders.
- Also suited for use on ½ ton LDV's & side-by-side / ATV
- Suitable as compact yet powerful washer or cleaner.

TYPICAL USERS:

- Forestry managers / contract managers / farmers / harvesting & silviculture contractors.

STANDARD FEATURES:

- Compact tank design with dimensions to suit Double Cab LDV load bin. Tanks manufactured from durable UV-stabilised Linear Low Density Polyethylene (LLDPE) material (3 year tank warranty against fractures and material failure).
- Sturdy Galvanized Top-Frame bolted to top of tank. Galvanized Top-Frame accommodates all assembled equipment.
- Unique base-plate design allows for secure fitment of engine and pump assembly.
- Honda GX160 (5.5Hp) recoil-start, petrol engine close-coupled to ML22X3 High Pressure piston pump. No V-belts or pulleys.
- 30m x 10mm Single Steel-braided high pressure hose with High Pressure quick couplings.
- Compact yet durable and sturdy heavy duty hose reel with hydraulic rotating coupling and manual rewind-handle
- 1 x G20 Aluminium pistol-grip discharge nozzle. (HP washing lance available on request).
- 4 x tie down eye-lids on top frame for secure fastening to your truck bed (tie down mounting kit available as optional extra) with rubber bump-stops to prevent impact to back of vehicle cab.



DIMENSIONS

	Length (L)	Width (W)	Tank Height (TH)	Total Height (H)
200 L Compact	980 mm	630 mm	430 mm	960 mm

HIGH PRESSURE STANDARD - PERFORMANCE:

- Maximum operating pressure - 40 Bar.
- Maximum discharge rate up to 18 L/min @ 40 Bar pressure (measured at nozzle)
- Effective discharge time of 11 minutes at max engine RPM with 200L capacity

