

## ANCO MANUFACTURING

2625 Theo Mocke Street, Piet Retief, 2380  
P.O. Box 882, Piet Retief, 2380, South Africa

Tel: +27 17 826 6023

[www.ancoman.co.za](http://www.ancoman.co.za)



## High Pressure Standard - Slip-on Unit *(Bakkie Sakkie)*

### TYPICAL APPLICATIONS:

- Forestry and veld fire applications where high pressure water delivery is required for clearing of under-brush and in lighter fuel load fires or typical grass fire situations.
- Also suitable as a high pressure washer / cleaner.

### TYPICAL USERS:

- Foresters / forestry contractors / first responders / fast attack teams / silviculture & harvesting contractors / farmers / agricultural contractors / light & medium industry / mining.

### STANDARD FEATURES:

- Unique T-tank design allowing fitment to any vehicle (fits between most wheel arches). Tanks manufactured from durable UV-stabilised Linear Low Density Polyethylene (LLDPE) material (3 year tank warranty against fractures and material failure)
- Sturdy Galvanized Top-Frame bolted to top of tank. Galvanized Top-Frame accommodates all assembled equipment.
- Unique base-plate design allows for secure fitment of engine and pump assembly.
- Honda GX160 (5.5Hp) recoil-start, petrol engine close-coupled to ML22X3 High Pressure piston pump. No V-belts or pulleys.
- Stainless Steel fair-lead roller guides to assist with hose deployment and retrieval – left and right



- 60m x 10mm Single Steel-braided high pressure hose with High Pressure quick couplings. 100m hose available as optional extra
- Durable and sturdy heavy duty hose reel with hydraulic rotating coupling and manual rewind - handle.
- 1 x G20 Aluminium pistol-grip discharge gun. (HP washing lance available on request).
- 4 x tie down eye-lids on top frame for secure fastening to your truck bed.

### TANK SIZES & DIMENSIONS

	Length (L)	Width (W)	Tank Height (TH)	Total Height (H)
400 L	1020 mm	1220 mm	400 mm	970 mm
500 L	1020 mm	1220 mm	470 mm	1040 mm
600 L	1020 mm	1220 mm	550 mm	1120 mm
700 L	1020 mm	1220 mm	620 mm	1190 mm

### HIGH PRESSURE STANDARD - PERFORMANCE:

- Maximum operating pressure - 40 Bar.
- Maximum discharge rate up to 25 L/min @ 40 Bar pressure

### OPTIONAL EXTRAS:

- ANCO Tank Baffles
- Truck-bed mounting kit
- PVC canvas pump & engine cover
- Venturi-suction system to allow suction from open water source
- Electric rewind hose reel

